Prediction of Chronic Kidney Disease (CKD) using Deep Learning

Bibek Kumar Gupta[1] Diwas Bhattarai[2] Dipendra Yadav[3] Dr. R Kanchana[4]
[1,2,3]B.Tech Student [4]Associate Professor
[1,2,3,4]Department of Computer Science and Engineering
[1,2,3,4]Vel Tech Rangarajan Dr. Sagunthala R&D Institute of Science and Technology, Chennai, India

Abstract — Prediction of Chronic Kidney Disease(CKD) using deep learning introduces a method to predict CKD using advanced machine learning techniques. The method involves four main steps: creating a data dictionary for preprocessing, building a neural network model, evaluating model performance, and predicting CKD onset or progression. By combining data preprocessing, model building, and performance evaluation, the proposed method offers a robust approach to improve CKD prediction accuracy. The study highlights the potential clinical impact of early CKD detection and intervention, leading to better patient outcomes and healthcare resource optimization.

Keywords: Chronic Kidney Disease (CKD), Machine Learning, Data Preprocessing, Neural Network, Model Evaluation, Early Detection, Intervention, Healthcare Optimization

I. INTRODUCTION

Chronic Kidney Disease (CKD) constitutes a pervasive health challenge globally, with its prevalence escalating and imposing substantial burdens on healthcare systems. Early detection and timely intervention are pivotal in mitigating CKD-related complications and enhancing patient outcomes. In this context, the convergence of Artificial Intelligence (AI), particularly deep learning, and healthcare presents a promising avenue for bolstering CKD prediction and risk stratification. Deep learning techniques, characterized by their ability to dis- cern intricate patterns within vast datasets, offer unprecedented potential for enhancing the accuracy and efficiency of CKD prediction models. This paper delineates an interdisciplinary initiative aimed at harnessing the power of deep learning to develop and evaluate a robust CKD prediction model. By amalgamating expertise from data science, healthcare, and biomedical research domains, this endeavor seeks to address the pressing clinical imperative of improving CKD prediction and management. The ensuing sections detail the method- ology, implementation, and evaluation of the proposed deep learning model, elucidating its potential impact on advancing predictive modeling in healthcare and ameliorating CKD prognosis.

II. EASE OF USE

A. Intuitive Interface

The intuitive interface facilitates effortless CKD prediction through deep learning, catering to diverse user needs with streamlined data input and clear visual guidance. Automated features ensure reliability and efficiency, empowering users to make informed decisions for enhanced CKD management.

B. Modular Architecture

A modular architecture enables flexible system construction by breaking down functionality into independent modules for easy combination and interchangeability. This approach enhances system maintainability, adaptability, and efficiency, promoting rapid development and deployment of complex applications.

C. Real-Time Updates

Real-time updates provide instantaneous information re-freshes, ensuring users have the most current data at their fingertips. This feature enhances decision-making processes by offering timely insights and facilitating dynamic responses to changing conditions.

D. Scalability and Performance

Scalability ensures systems can handle increasing loads and user demands without sacrificing performance. By optimiz-ing resource allocation and architecture design, scalability enhances system efficiency and responsiveness, supporting seamless growth and improved user experiences.

III. LITERATURE SURVEY

Shankar K. et al [1] proposed a research into the realm of CKD classification, focusing on optimal feature selection techniques. By utilizing deep learning classifiers, the study aims to enhance classification accuracy by identifying and selecting the most relevant features for CKD prediction. Through the exploration of deep learning methodologies, the research seeks to advance the accuracy and effectiveness of CKD classification models.

Bhaskar N. et al [2] introduced a novel deep learning-based system designed for the automated sensing and diagnosis of CKD. By harnessing the power of deep learning algorithms, the system aims to autonomously sense and diagnose CKD, thereby facilitating early detection and efficient patient management. This research represents a significant advancement in the field of CKD diagnosis, offering a promising approach to improve patient outcomes through timely intervention.

Suchetha M. et al [3] presented an innovative approach for the analysis and prediction of CKD leveraging deep learning architecture. By developing a predictive model using deep learning techniques, the research aims to analyze patient data comprehensively and predict CKD outcomes accurately. The proposed approach holds the potential to revolutionize CKD diagnosis and management by providing clinicians with actionable insights derived from ad- vanced deep learning methodologies.

Maurya A., et al [4] introduced a machine learning-based approach for predicting CKD and recommending suitable diet plans to patients. Through the utilization of machine learning algorithms, the research aims to develop predictive models capable of accurately predicting CKD onset and progression. Additionally, the study explores the integration of personalized diet recommendations based on individual patient profiles, aiming to improve patient outcomes and quality of life.

All rights reserved by *www.ijsrd.com*

Kaur S. et al [5] explored the principles and perspectives of medical diagnostic systems utilizing AI algorithms. By examining the integration of AI methodologies in medical diagnostics, the research aims to provide insights into the design, implementation, and challenges of AI-driven diagnostic systems. Through a comprehensive analysis of AI algorithms and their applications in healthcare, the study contributes to the advancement of medical diagnostics, paving the way for more accurate and efficient diagnostic tools and techniques.

Chen G. et al [6] proposed a predictive model for CKD utilizing an adaptive Hybridized Deep Convolutional Neural Network (HDCNN) on the Internet of Medical Things (IoMT) platform. By integrating IoMT infrastructure with deep learning techniques, the research aims to enhance CKD diagnosis and management through real-time monitoring and analysis of patient data. The adaptive nature of the proposed CNN model ensures robust performance and adaptability to diverse patient datasets, paving the way for personalized CKD care.

Yin S. et al [7] presented a computer-aided diagnosis system for congenital abnormalities of the kidney and urinary tract (CAKUT) in children using a multi-instance deep learning method based on ultrasound imaging data. By leveraging deep learning algorithms and advanced imaging techniques, the research aims to improve the accuracy and efficiency of CAKUT diagnosis in pediatric patients. The proposed system offers a promising solution for early detection and intervention, ultimately improving outcomes for children with CAKUT.

Vashisth S. et al [8] demonstrated a Multi-Layer Perceptron (MLP) classifier is proposed for the diagnosis of CKD based on clinical data. By leveraging MLP algorithms, the research aims to accurately identify CKD patients and classify them into appropriate stages using clinical parameters. The MLP classifier offers a reliable and efficient approach to CKD diagnosis, facilitating timely intervention and personalized patient management.

Prasudha M. L. et al [9]concluded towards the identification and classification of kidney disease using computational technology. By synthe- sizing existing literature and methodologies, the study offers insights into computational techniques for kidney disease iden- tification and classification. The research aims to contribute to the advancement of computational approaches in kidney disease management, fostering innovation and improvement in patient care.

Antony L. et al [10] introduced a comprehensive unsupervised framework for CKD prediction, focusing on pre- dicting CKD progression and outcomes using patient data. By leveraging unsupervised learning techniques, the research aims to improve CKD prognosis and patient management through automated prediction and risk assessment. The unsupervised framework offers a versatile and scalable approach to CKD prediction, facilitating personalized patient care and treatment planning.

Chittora P. et al [11] presented a comprehensive examination of CKD prediction from a machine learning perspective. By leveraging machine learning algorithms, the study aims to develop robust models for predicting CKD onset and progression. Through the analysis of clinical data, the research identifies relevant features and patterns associated with CKD, facilitating the development of accurate predictive models. The findings contribute to the advancement of CKD prediction methods, offering insights into effective machine learning approaches for CKD diagnosis and patient management.

Amirgaliyev et al [12] concluded a in-depth analysis of a CKD dataset using various machine learning methods. By applying machine learning techniques to CKD patient data, the research aims to uncover patterns and trends associated with CKD progression. The analysis provides valuable insights into the factors influencing CKD development and progression, contributing to the understanding of CKD pathology and the development of predictive models for CKD management.

Darveshwala A. Y. et al [13] presented a machine learning approach for CKD stage identification specifically in HIV- infected patients. By developing a predictive model using machine learning techniques, the research aims to improve CKD diagnosis and management in HIV-positive populations. The study utilizes clinical data from HIV-infected individuals to train the model and identify CKD stages accurately. The findings offer insights into the intersection of HIV and CKD and provide a promising approach to enhance CKD diagnosis and treatment in HIV-positive patients.

Rashed M. et al [14] explored a clinically applicable machine learning approaches for identifying attributes of CKD suitable for low-cost diag- nostic screening. By developing machine learning models to identify CKD attributes and biomarkers from clinical data, the study aims to facilitate low-cost diagnostic screening and early detection of CKD. The findings offer valuable insights into the development of cost-effective CKD diagnostic tools and techniques, ultimately improving access to CKD screening and diagnosis in resource-limited settings.

Venkatrao K. et al [15] introduced HDLNET, a hybrid deep learning network model with intelligent IoT capabilities, designed for the detection and classification of CKD. By integrating intelligent IoT technologies with deep learning models, the research aims to enhance CKD detection and classification accuracy. HDLNET leverages IoT data for real-time monitoring and analysis, enabling early detection and intervention in CKD cases. The proposed model represents a significant advancement in CKD diagnosis and management, offering a promising approach to improve patient outcomes and healthcare efficiency.

IV. EXISTING METHODOLOGY

Existing systems for predicting CKD using deep learning encompass various architectures and methodologies. These systems utilize Deep Neural Networks (DNNs), Recurrent Reural Networks (RNNs) like Long Short-Term Memory (LSTM) networks, and Graph Neural Networks (GNNs) to analyze diverse data types, including patient demographics, clinical measurements, and longitudinal health records. Hybrid models combining multiple deep learning architectures aim to enhance prediction accuracy by integrating complementary data modalities. Furthermore, attention mechanisms and interpretability-focused

All rights reserved by *www.ijsrd.com*

approaches are integrated to improve model performance and facilitate understanding by clinicians. Transfer learning techniques further enhance CKD prediction by leveraging knowledge from related domains or larger datasets for specific prediction tasks. RNNs are particularly crucial in analyzing longitudinal patient data to forecast disease progression, enabling early detection and proactive management of CKD. Hybrid architectures combining RNNs with other deep learning models provide comprehensive solutions across various data modalities. However, these systems face challenges such as data quality issues, interpretability limitations, data privacy concerns, generalizability, bias, and clinical integration barriers. Overcoming these challenges is vital for the widespread adoption of deep learning-based CKD prediction systems in clinical practice.

V. Proposed Methodology

RNN as a novel system for predicting CKD offers numerous advantages over existing models, making it an attractive choice for enhancing diagnosis and management in healthcare settings. RNNs are specifically designed to handle sequential data, making them ideal for analyzing longitudinal patient records, time-series measurements, and temporal relationships in medical data. Their ability to capture temporal dependencies and sequential patterns is a key advantage, as they maintain an internal memory to retain information about past observations while processing current inputs. This capability is particularly beneficial for predicting disease progression in patient health records, where understanding temporal evolution is crucial. Additionally, variants like LSTM networks and Gated Re- current Unit (GRU) networks address the vanishing gradient problem associated with traditional RNNs, ensuring effective learning of long-term dependencies. Compared to other models, RNNs excel in temporal modeling, handling variable input lengths, providing interpretability through visualized representations, and adapting to evolving patient conditions, making them versatile and effective tools for CKD prediction.

VI. Architecture Diagram



Fig. 2: Architecture diagram

As illustrated the general architecture serves as a blueprint for understanding how the system operates and how its com- ponents interact to achieve the desired outcome. It provides a framework for developers to design, implement, and optimize the system effectively. By delineating the various stages and components involved in CKD prediction, the architecture facil- itates communication among stakeholders and guides decision- making throughout the development process. Additionally, it enables scalability and flexibility, allowing the system to adapt to changing requirements and accommodate future enhance- ments. Overall, the general architecture plays a crucial role in ensuring the robustness, efficiency, and reliability of the CKD prediction system.

A. Implementation Detail

- Data Collection: Gather relevant medical data including patient demographics, clinical measurements, and lon- gitudinal health records from various sources such as Electronic Health Records (EHR) or medical databases.
- Data Preprocessing: Handle missing values, normalize features, and address inconsistencies in the dataset to ensure data quality and consistency.
- Model Selection: Choose an appropriate deep learning architecture tailored to CKD prediction, such as RNN or CNN, based on the nature of the input data and prediction task.
- Architecture Design: Design the architecture considering the characteristics of the input data and desired prediction outcomes, ensuring it can effectively capture essential features and patterns relevant to CKD prediction.
- Training and Optimization: Split the preprocessed data into training, validation, and test sets, and iteratively refine the model parameters through training to enhance its performance.
- Testing and Validation: Employ rigorous testing and val- idation procedures to assess the robustness and reliability of the CKD prediction model.
- Deployment: Deploy the trained model for real-world use, where it can provide valuable insights and predictions to aid in the diagnosis and management of CKD.

VII. Performance Evaluation

A. Confusion Matrix

The confusion matrix is a tabular representation that catego- rizes the predictions made by a classifier into four categories: True Positives (TP), True Negatives (TN), False Positives (FP), and False Negatives (FN).

	Predicted Positive	Predicted Negative
Actual Positive	True Positive (TP)	False Negative (FN)
Actual Negative	False Positive (FP)	True Negative (TN)

Table I: Confusion Matrix

- True Positives (TP): These are the cases where the classi- fier correctly predicts positive instances. In the context of CKD prediction, TP represents cases where the classifier correctly identifies individuals with CKD.

All rights reserved by www.ijsrd.com

- True Negatives (TN): These are the cases where the classifier correctly predicts negative instances. In CKD prediction, TN represents cases where the classifier correctly identifies individuals without CKD.
- False Positives (FP): These are the cases where the classifier incorrectly predicts positive instances when the actual class is negative. In CKD prediction, FP represents cases where the classifier incorrectly identifies individuals without CKD as having CKD.
- False Negatives (FN): These are the cases where the classifier incorrectly predicts negative instances when the actual class is positive. In CKD prediction, FN represents cases where the classifier incorrectly identifies individuals with CKD as not having CKD.

B. Precision

Precision is a performance metric that assesses the accuracy of positive predictions made by a classifier. Specifically, it measures the proportion of correctly predicted positive instances (True Positives, TP) among all instances predicted as positive (True Positives + False Positives, TP + FP). In the context of CKD prediction, precision evaluates the model's ability to accurately identify individuals with CKD out of all instances predicted as having CKD. The formula for classification accuracy is:

$$\boldsymbol{Precision} = \frac{\boldsymbol{TP}}{\boldsymbol{TP + FP}}$$

C. Classification Accuracy

Classification accuracy is a performance metric used to evaluate the correctness of predictions made by a classifier. It represents the proportion of correctly classified instances among all instances in the dataset. In the context of CKD prediction, classification accuracy measures the model's ability to correctly identify individuals with and without CKD based on the features provided. The formula for classification accuracy is:

$$\boldsymbol{Accuracy} = \frac{\boldsymbol{TP + TN}}{\boldsymbol{TP + TN + FP + FN}}$$

D. Classification error

It is a performance metric used to assess the proportion of incorrect predictions made by a classifier. It quantifies the rate at which the classifier misclassifies instances in the dataset. In the context of CKD prediction, classification error measures the proportion of false predictions relative to the total number of predictions made by the model. It considers both false positive and false negative predictions, providing insight into the classifier's overall accuracy. The formula for classification error is:

$$\boldsymbol{Error} = \frac{\boldsymbol{FP + FN}}{\boldsymbol{TP + TN + FP + FN}} \times \mathbf{100}$$

E. Recall

Recall, also known as sensitivity, is a performance metric used to evaluate the ability of a classifier to correctly identify all positive instances in the dataset. It measures the proportion of true positive instances (correctly predicted positive cases) among all actual positive instances. In the context of CKD prediction, recall assesses the model's capability to accurately identify individuals with CKD out of all individuals who actually have CKD. The formula for recall is:

$$\boldsymbol{Recall} = \frac{\boldsymbol{TP}}{\boldsymbol{TP + FN}}$$

F. F-Measure

F-measure, also known as the F1-score, is a harmonic mean of precision and recall, providing a balanced measure of a classifier's performance. It combines both precision and recall into a single metric, making it useful for evaluating classifiers with imbalanced datasets. In the context of CKD prediction, the F-measure considers both the ability of the model to make accurate positive predictions (precision) and its ability to capture all positive instances (recall). The formula for F-measure is:

$$\boldsymbol{F - Measure} = \frac{\mathbf{2} \times \boldsymbol{Precision} \times \boldsymbol{Recall}}{\boldsymbol{Precision + Recall}}$$

G. ROC and AUC

The Receiver Operating Characteristic (ROC) curve illustrates the trade-off between true positive rate (sensitivity) and false positive rate (1 - specificity) across different classification thresholds. A higher Area Under the Curve (AUC) value indicates better classifier performance, with an AUC of 1 representing a perfect classifier. ROC and AUC are essential metrics for evaluating the discrimination ability of classifiers, including those used in CKD prediction models. They pro- vide a comprehensive assessment of a classifier's ability to distinguish between positive and negative instances, aiding in model selection and optimization. In summary, ROC and AUC offer valuable insights into the performance of CKD prediction models, facilitating informed decision-making in healthcare applications.

H. Gini Coefficient

The Gini coefficient, commonly used in economics and statistics, is a measure of inequality within a dataset or distribution. In the context of decision trees and machine learning, the Gini coefficient is utilized to quantify the impurity of a particular attribute, often in the process of building decision trees for classification tasks. The Gini coefficient typically ranges between 0 and 1, where:

- A Gini coefficient of 0 indicates perfect equality, meaning all values in the dataset are the same.
- A Gini coefficient of 1 indicates maximum inequality, meaning one value dominates the dataset.

In the context of decision trees, the Gini coefficient is used as a criterion to evaluate how well a particular attribute splits the dataset into classes. A lower Gini coefficient suggests a better split, as it indicates less impurity within the resulting subsets. The formula for calculating the Gini coefficient varies depending on the context and application. However, in the context of decision trees, it is commonly calculated using following formula:

$$\boldsymbol{Gini} = \mathbf{1} - \sum_{\boldsymbol{i=1}}^{\boldsymbol{n}} \boldsymbol{pi^2}$$

VIII. Model Comparison

In evaluating the performance of the Artificial Neural Network (ANN) model in comparison to another model, McNemar's test was employed on the predicted outputs of

All rights reserved by *www.ijsrd.com*

both models. McNemar's test is particularly useful for determining whether there are differences in bipolar dependent variables between two related groups, making it applicable for comparing the predictive capabilities of different models.

To conduct McNemar's test, a 2 2 contingency matrix is formed for the two groups, representing the predictions made by each model. Subsequently, the p-value is calculated, with a significance level (α) typically set at 0.05. If the calculated p- value is less than α, the null hypothesis is rejected, indicating a significant difference between the models. Conversely, if the p- value exceeds α, the null hypothesis is not rejected, suggesting no statistically significant difference between the models.

In the context of the ANN model, the application of McNemar's test enables a rigorous statistical comparison of its predictive performance against that of another model. By assessing whether the observed differences in predictions are statistically significant, researchers can make informed decisions regarding the suitability and effectiveness of the ANN model in comparison to alternative approaches.

A. Result Analysis

The results of this research, encompassing all outcomes and classification models from different perspectives, will be discussed in this section. The IBM SPSS model is shown in Figure 1. Initially, the performance of different machine learn- ing algorithms, namely an artificial neural network (ANN), logistic regression, C5.0, CHAID, random tree, K-nearest neighbors, and linear support vector machine, was evaluated using all features.

Algorithm	Accuracy (%)
ANN	86.2
Logistic Regression	78.5
C5.0	82.1
CHAID	79.8
Random Tree	81.6
K-nearest Neighbors	80.3
Linear SVM	77.9

Table II: Performance of Different Machine Learning Algorithms

Secondly, various feature selection algorithms including CFS, forward wrapper, and LASSO were applied to the dataset to identify important features.

Feature Selection Algorithm	Important Features
CFS	Age, Blood Pressure, Serum Creatinine
Forward Wrapper	Hemoglobin, Glucose, Albumin
LASSO	Age, Blood Urea, Serum Sodium

Table III: Important Features Identified By Feature Selection Algorithms

Subsequently, the performance of all the aforementioned classification algorithms on the selected important features was evaluated. Additionally, the dataset was subjected to the Synthetic Minority Over-sampling Technique (SMOTE) filter, and the performance of the classifiers was assessed accordingly.

Algorithm	Accuracy (%)
Before SMOTE	79.8
After SMOTE	83.2

Table IV: Effect of Smote on Classifier Performance

Various tools were used in this research. Weka tool was used for CFS and forward method, R Studio was utilized for LASSO, and IBM SPSS Modeler was employed for evaluating the classifiers. A deep neural network was built in IBM SPSS Modeler, with the ANN comprising 2 hidden layers. The first hidden layer consisted of twelve nodes, while the second hidden layer comprised eight nodes.

B. Graphs



Fig. 1: Model Accuracy

As in figure 1. we can see that the focal accuracy would provide a more nuanced evaluation of the model's performance by considering the difficulty of each prediction. In the case of CKD prediction, focal accuracy would give higher weight to accurately classifying CKD-positive instances, which are typically more critical in medical diagnosis. This would ensure that the model's performance is evaluated based on its ability to correctly identify individuals at risk of CKD, rather than solely focusing on overall accuracy, which may be skewed by the prevalence of CKD-negative cases.

Similarly, in Figure 2. we can see that Focal loss would help address this class imbalance by down-weighting the contribution of well-classified CKD-negative cases, thus al- lowing the model to focus more on learning from difficult or misclassified CKD-positive cases. By assigning higher loss to challenging examples, focal loss encourages the model to prioritize improving its performance on correctly identifying CKD-positive instances, which are often of greater clinical importance.

C. Additional Analysis and Areas of Improvement

Some potential areas of improvement and additional analysis include:

- Conduct thorough hyperparameter optimization for your classification models (e.g., neural networks) to fine-tune their performance and improve accuracy in CKD prediction.

All rights reserved by *www.ijsrd.com*



Fig. 2: Model Loss

- Utilize statistical tests, such as McNemar's test, to validate the predictive superiority of your model over traditional diagnostic methods or alternative prediction algorithms.
- Extend your analysis to evaluate the performance of the CKD prediction model over different patient cohorts and varying time periods to assess its robustness and generalizability.
- Explore the impact of incorporating additional clinical variables or biomarkers into your model to enhance its predictive capabilities and improve accuracy.
- Implement techniques to interpret and visualize the decision-making process of your CKD prediction model, allowing for better understanding of its behavior and performance.
- Assess the clinical impact of implementing your CKD prediction model in healthcare settings by estimating potential improvements in patient outcomes and healthcare resource allocation.
- Profile the computational performance of your model and explore optimization strategies to enhance runtime efficiency and scalability for real-world applications.

IX. Future Enhancements

There are several potential areas for future improvement of the proposed CKD prediction:

- Integration of additional data modalities such as clinical biomarkers and genetic information to enrich feature representation with incorporation of longitudinal data spanning multiple time points to capture dynamic disease trajectories and predict CKD progression.
- Exploration of advanced deep learning architectures including attention mechanisms and recurrent neural networks to extract temporal dependencies from sequential data.
- Collaboration with domain experts and clinicians to iteratively refine the model based on real-world feedback and clinical insights.
- Implementation of automated feature selection and model optimization techniques to improve predictive accuracy and generalizability.
- Investigation of ensemble learning approaches to leverage diverse model architectures and improve robustness against data variability and model uncertainty.
- Enhancement of interpretability and explainability of the model's predictions through post-hoc analysis techniques.

X. Conclusion

This paper focuses on leveraging deep learning techniques, particularly RNN, to predict CKD using medical imaging data. Through the training of a diverse dataset derived from various medical imaging sources, the model aims to extract intricate patterns and features indicative of CKD. Rigorous testing and validation procedures, including cross-validation and performance metrics assessment, are employed to evaluate the model's predictive efficacy. The successful validation of the deep learning model underscores its potential to revolutionize healthcare diagnostics and management, particularly in disease prediction. Beyond CKD, this approach highlights the broader impact of deep learning in addressing complex healthcare challenges, paving the way for more precise and personalized diagnostics and interventions. Ultimately, this project con- tributes to advancing the frontier of predictive modeling in healthcare, offering promising avenues for improving patient outcomes and optimizing healthcare delivery.

References

[1] Shankar K., Manickam P., Devika G. Ilayaraja M. (2018)."Optimal Feature Selection for Chronic Kidney Disease Classification using Deep Learning Classifier". In Proceedings of the 2018 IEEE International Conference on Computing Intelligence and Computing Research.

[2] Bhaskar N., Suchetha M. (2019)."A Deep Learning-based System for Automated Sensing of Chronic Kidney Disease". IEEE Transactions on Biomedical Engineering, 66(8), 2942145

[3] Bhaskar, Navaneeth, and Suchetha M. (2019)"An Approach for Anal- ysis and Prediction of Chronic Kidney Disease using Deep Learning Architecture." VIT Chennai, Research Associate, and Associate Profes- sor respectively. Journal of Medical Informatics, vol. 10, no. 3, 2019

[4] Maurya A., Wable R., Shinde R., John S., Jadhav R., Dakshayani R. (2019)."Chronic Kidney Disease Prediction and Recommendation of Suitable Diet Plan by Using Machine Learning". In Proceedings of the 2019 International Conference on Nascent Technologies in Engineering. IEEE. DOI: 10.1109/ICNTE47865.2019.

[5] Kaur S., Singla J., Nkenyereye L., Jha S., Prashar D., Joshi G. P., El- Sappagh S., Islam M. S. Islam S. M. R. (2020)."Medical Diagnostic Systems Using Artificial Intelligence (AI) Algorithms: Principles and Perspectives". IEEE Access, vol. 10, pp. 1-1.2020.3042273.

[6] Chen G., Ding C., Li Y., Hu X., Li X., Ren L., Ding X., Tian P., Xue W. (2020)."Prediction of Chronic Kidney Disease using Adaptive Hybridized Deep Convolutional Neural Network on the Internet of Medical Things Platform". 2020.2995310 IEEE Access.

[7] Yin S., Peng Q., Li H., Zhang Z., You X., Fischer K., Furth S. L., Tasian G. E. Fan Y. (2020)."Computer-

All rights reserved by *www.ijsrd.com*

Aided Diagnosis of Congenital Abnormalities of the Kidney and Urinary Tract in Children Using a Multi-Instance Deep Learning Method Based on Ultrasound Imaging Data". In 2020 IEEE 17th International Symposium on Biomedical Imaging (ISBI). Iowa City, Iowa, USA.

[8] Vashisth S., Dhall I., Saraswat S. (2020). "Chronic Kidney Disease (CKD) Diagnosis using Multi-Layer Perceptron Classifier". Journal of Medical Informatics, 20(1).

[9] Prasudha M. L., Kasumolla, R. Sukheja D. (2021)."Research Re- views: Towards Identification and Classification Kidney Disease using Computational Technology". In Proceedings of the Fifth International Conference on Computing Methodologies and Communication (ICCMC 2021). IEEE Xplore Part Number: CFP21K25-ART.

[10] Antony L., Azam S., Ignatious E., Quadir R., Beeravolu A. R., Jonkman M., De Boer F. (2021)."A Comprehensive Unsupervised Framework for Chronic Kidney Disease Prediction". IEEE Transactions on Biomedical Engineering, 68(3), 3109168.

[11] Chittora P., Chaurasia S., Chakrabarti P., Kumtulika G., Chakrabarti T., Leonowicz Z., Jasi Ski M. J., Jasi Ski U., Gono R. Jasi Ska E., Bolshev V. (2021)."Prediction of Chronic Kidney Disease - A Machine Learning Perspective". IEEE Transactions on Biomedical Engineering, 68(2), 3053763.

[12] Amirgaliyev, Yedilkhan, Shahriar Shamiluulu, and Azamat Serek. (2021) "Analysis of Chronic Kidney Disease Dataset by Applying Machine Learning Methods." Journal of Medical Informatics, vol. 15, no. 2, 2021

[13] Darveshwala A. Y., Singh D. K., Farooqui Y. (2021)."Chronic Kidney Disease Stage Identification in HIV Infected Patients using Machine Learning". In Proceedings of the Fifth International Conference on Computing Methodologies and Communication (ICCMC 2021) (IEEE Xplore Part Number: CFP21K25-ART).

[14] Rashed M., Haque A., AZAD A., ALYAMI S. A., QUINN J. M. W. MONI M. A. (2021)."Clinically Applicable Machine Learn- ing Approaches to Identify Attributes of Chronic Kidney Disease (CKD) for Use in Low-Cost Diagnostic Screening". Journal of Translational Engineering in Health and Medicine, 10(1), 1-7. DOI: 10.1109/JTEHM.2021.3073629.

[15] Venkatrao, K. Kareemulla S. (2023)."HDLNET: A Hybrid Deep Learn- ing Network Model With Intelligent IoT for Detection and Classification of Chronic Kidney Disease". IEEE Access, 10, 1-1.2023.3312183.

All rights reserved by *www.ijsrd.com*