

Review Paper on Development of Forgeries Digital Images by Using Illumination Color Classification

Ajeet kumar¹ Ms.P.V.Gawande²

^{1,2}Department of Electronics and Telecommunication

^{1,2}Priyadarshini Bhagwati College of Engineering Nagpur, India

Abstract— Interruption or manipulation in the digital photographs becomes a common problem in multimedia communication. Interrupted digital images can be rectified with the illumination color classification method. Over the years, photographs have been used as document of events as well as proof in legal proceedings. Although some of photographers are able to manipulate the images and make composites of original images, this process requires expert knowledge and demands lot of time. In today's world, a lot of skillfully developed image editing software's are available which makes image manipulation and modifications an easy task. This reduces trust in photographs and presents an open question on authenticity of images and photographs. This paper, aims at focusing on the most common forms of image manipulation, which is called as image splicing. Here we propose a forgery detection method which uses inconsistencies in illumination of images. For achieving this, we make use of physics and statistics based illuminant estimators. These illuminant estimates are used to extract features which are then given to a machine-learning technique which supports us in decision-making.

Key words: Illuminant estimation, Face extraction, Paired face features, Support vector machine

I. INTRODUCTION

Today is the world of multimedia communication .Analog and digital photos or images are the best tools for sending the information in multimedia communication .Now a days there are various photo editing software's or applications are present which can interrupt the original photos by adding or subtracting some part of that particular digital images. Suppose a person snapped some photos with digital cameras and stored that particular photos in a memory device.

One the another part suppose a criminal minded person edits that photo and make it vulgarish.

Is is the good work ,no absolutely not ,this is against the honour and respect of any person.

The question arises that how we can rectify which one photos are original, the answer is that illumination color classification method. A large number of digital and analog images are captured and produced by a wider range of electronic devices and gadgets such as cameras handheld multimedia devices, computers. Image and photographs are distributed across the globe via various means of communication. World Wide Web plays a major role in establishing communication and distributing the documents among the masses. "Whoever said the camera never lies was a liar". Nowadays, it is very easy to use image processing techniques to manipulate images; image editing software makes the modification and manipulation an easier job. However, before considering an image inappropriate or taking actions on any image, one must confirm whether the image has been altered or is a composite image. Image splicing is image manipulation technique which is a

commonly used. To determine whether the image is authentic or not, forensic investigators use a number of sources for assessment of alteration in an image.

In this work, we make an important step towards minimizing user interaction for an illuminant-based tampering decision- making. We propose a new semiautomatic method that is also significantly more reliable than earlier approaches. Quantitative evaluation shows that the proposed method achieves a detection rate of 86%, while existing illumination-based work is slightly better than guessing. We exploit the fact that local illuminant estimates are most discriminative when comparing objects of the same (or similar) material. Thus, we focus on the automated comparison of human skin, and more specifically faces, to classify the illumination on a pair of faces as either consistent or inconsistent. User interaction is limited to marking bounding boxes around the faces in an image under investigation. In the simplest case, this reduces to specifying two corners (upper left and lower right) of a bounding box.

In summary, the main contributions of this work are:

- Interpretation of the illumination distribution as object texture for feature computation.
- A novel edge-based characterization method for illuminant maps which explores edge attributes related to the illumination process



Fig. 1: Example Illuminant Map That Directly Shows an Inconsistency.




Fig. 2: Overview of the proposed method.

II. OVERVIEW AND ALGORITHMIC DETAILS

We classify the illumination for each pair of faces in the image as either consistent or inconsistent. Throughout the paper, we abbreviate illuminant estimation as IE, and illuminant maps as IM. The proposed method consists of five main components:

- 1) **Dense Local Illuminant Estimation (IE):** The input image is segmented into homogeneous regions. Per illuminant estimator, a new image is created where each region is colored with the extracted illuminant color. This resulting intermediate representation is called illuminant map (IM).
- 2) **Face Extraction:** This is the only step that may require human interaction. An operator sets a bounding box around each face (e.g., by clicking on two corners of the bounding box) in the image that should be investigated. Alternatively, an automated face detector can be employed. We then crop every bounding box out of each illuminant map, so that only the illuminant estimates of the face regions remain.
- 3) **Computation of Illuminant Features:** for all face regions, texture-based and gradient-based features are computed on the IM values. Each one of them encodes complementary information for classification.
- 4) **Paired Face Features:** Our goal is to assess whether a pair of faces in an image is consistently illuminated. For an image with faces, we construct joint feature vectors, consisting of all possible pairs of faces.
- 5) **Classification:** We use a machine learning approach to automatically classify the feature vectors. We consider an image as a forgery if at least one pair of faces in the image is classified as inconsistently illuminated.

III. METHODOLOGY

A. Dense Local Illuminant Estimation:

The input image is segmented into a specific type of regions, which are the regions of similar constant hue, by using algorithm suggested by by Felzenszwalb and Huttenlocher [5]. For each such regions mentioned above, illuminant color of the regions is calculated. The generalized grey world estimates is one color estimator and an estimate based on physics which is called as inverse-intensity chromaticity space estimator are used for obtaining the illumination estimates. The two illuminant maps are obtained by recoloring the regions with similar hue. The both illuminant maps obtained are then examined individually afterwards.

Inverse Intensity-Chromaticity Estimates . In this approach, the image intensities which obtained are assumed to show a combination of diffuse and specular reflectance. Diffuse reflection is the reflection of light from a surface such that an incident ray is reflected at many angles .Specular reflection is the mirror-like reflection of light , in which light ray coming from solitary direction is reflected into solitary outgoing direction. Crisp specularities are presumed to be composed of only the color of the illuminant. Riess and Angelopoulou [7] suggested a technique to compute these estimates in an image in small regions. In the voting procedure, two conditions are enforced on a small region to increase flexibility with induced noises. If a small region does not fulfill the conditions stated above, then such small regions are decategorized from voting procedure. The illuminant is based on majority votes of the obtained estimates.

IV. FACE EXTRACTION

It is needed that all the faces in an image or photograph that are needed for consideration should be enclosed with the bounding boxes .The bounding boxes can be procured by using an automated algorithm by Schwartz et. al.[8] or a human operator is chosen for bounding boxes. The advantages using a human operator for bounding boxes are that a human is better at judging the area of face to be enclosed in bounding boxes, reduces missed faces as well as false detection of faces another reason for preferring human over automated algorithm is the scene context is crucial in determining the lighting situation. Given a scenario there is an image where all persons under consideration are illuminated by the single source of light. The illuminants are expected to be similar. On the contrary, assuming that a person in the foreground is illuminated by camera flashlight and a person in the background is illuminated by surroundings light. There will be dissimilarity in the color of the illuminants is presumed. This small dissimilarity are difficult to figure out in a fully automated technique, but this can be eliminated with the human intervention.

V. INTERPRETATION OF ILLUMINANT EDGES

A. Extraction of Edge Points:

The Canny edge detector[9] used for obtaining edge points from the illuminant map of the face region, which gives edge points that are close in distance to each others. The number of edge point obtained may be large for minimizing the number of edge points; an approach is applied on the output of the Canny edge detector. A starting point is selected as a

seed point, all other edge pixels in a region of interest which are centered around the seed point are then discarded from the process. The edge points nearer to region of interest are elected as seed points for the next step. This operation is repeated on the whole image till number of points are minimized and it is assured that every face region has similar or approximate density of points.

B. Point Description:

The Histograms of Oriented Gradients is computed which gives description about the distribution of the chosen edge points. This Histograms of Oriented Gradients uses the concept of normalized local histograms as a basis for obtaining image gradient orientations. The HOG descriptor is built neighboring every edge points. The area around of this type of an edge point is called as cell. Each cell gives localized 1-D histogram of quantized gradient directions. The feature vector for this obtained feature descriptor is created by combining the histograms of all cells which are distributed in spatially larger region, of which histogram contrast is normalized. The output of this Histograms of Oriented Gradients is used as feature vector for the next steps.

C. Visual Vocabulary:

The number HOG vectors that are obtained differs, which is contingent upon the size and structure of the face which is being analyzed. The visual dictionaries as suggested by Csurka et. al.[10] are created to get feature vectors of specified length. This Visual dictionaries form a powerful representation, in which every face is assumed as a group of region descriptors. The spatial location of each of this region is eliminated [11]. The visual dictionary is built by subdividing the data given for training into feature vectors of original and altered images. Every group is then clustered into clusters by applying the k-means algorithm [12].After applying k-means a visual dictionary is built using the visual words, where every word is characterized by the center of the cluster. By this, the most representative feature vectors of the training set are epitomized by the visual dictionary.

D. Quantization Using The Precomputed Visual Dictionary:

The HOG feature vectors obtained are then mapped to the visual dictionary. Every feature vector in an image is characterized by the nearest word in the dictionary which is the distance of Euclidean norm. A histogram is obtained for the word counts in the dictionary which in turn represents the distribution of HOG feature vectors in a face of the image.

E. Texture Description:

The SASI Statistical Analysis of Structural Information descriptor suggested by Carkacioglu and Yarman-Vural [4] which is used for obtaining information regarding the image from illuminant maps. Penatti [13] suggested that this descriptor gives good performance. The salient aspect of using this descriptor is its ability to detect discontinuities in patterns of texture and capture minute granular information. Dissimilar illuminant colors interact varying with the surfaces differing in types, which gives dissimilar illumination. This descriptor estimates structural attributes of textures, which is uses the information from autocorrelation of horizontal, vertical and diagonal pixel lines at different scales. Another autocorrelation is calculated on the basis of specific fixed orientation, scale, and shift. The mean and

standard deviation of all pixel values gives two feature aspects. This process is repeated for calculating different orientations, scales and shifts and applied till it gives a 128-dimensional feature vector. In the last step the obtained feature vector normalization is done.

F. Paired Faces:

The same descriptors for each of the two faces are merged for analyzing and comparing the two faces. The SASI-descriptors obtained on gray world can be Coupled together for similarity. The scheme behind this is a feature concatenation from two faces is distinct when one of the faces is an original and another is doctored one. The Statistical Analysis of Structural Information descriptor and Histograms of Oriented Gradients edge descriptors seize two varying attributes of the face regions. The both descriptors can be imagined are digital signatures with distinct operations in digital signal processing context. The average value and standard deviation for each feature dimension is calculated. The feature dimensions with the max difference in the average values for are considered.

VI. CLASSIFICATION

The illumination for every pair of faces in an photograph or image can be categorized as consistent or inconsistent. By supposing that all chosen faces are illuminated by the same lighting conditions, the image labeled as doctored if a pair is categorized as inconsistent, the discrete feature vectors are categorized by utilizing support vector machine classifier which makes use of radial basis function kernel. The SASI feature and HOG edge features impart information that are supportive of each other .A technique based on machine learning is used for improving the detection performance. Ludwig et al. suggested a technique that can be used which a late fusion technique is named SVM-Meta Fusion. Every combination of illuminant map and feature type are separately classified by making use of 2- class SVM classifier to for getting the distance between the image's feature vectors and the classifier decision boundary. The marginal distances provided by all individual classifiers to build a new feature vectors are combined by SVM-Meta Fusion.

VII. CONCLUSION

we presented a new method for detecting forged images of people using the illuminant color. We estimate the illuminant color using a statistical gray edge method and a physics-based method which exploits the inverse intensity-chromaticity color space. We treat these illuminant maps as texture maps. We also extract information on the distribution of edges on these maps.

REFERENCES

- [1] A. Rocha, W. Scheirer, T. E. Boult, and S. Goldenstein, "Vision of the unseen: Current trends and challenges in digital image and video forensics," *ACM Comput. Surveys*, vol. 43, pp. 1–42, 2011.
- [2] P. Saboia, T. Carvalho, and A. Rocha, "Eye specular highlights telltales for digital forensics: A machine learning approach," in *Proc. IEEE Int. Conf. Image Processing (ICIP)*, 2011, pp. 1937–1940.

- [3] C. Riess and E. Angelopoulou, "Physics-based illuminant color estimation as an image semantics clue," in Proc. IEEE Int. Conf. Image Processing, Nov. 2009, pp. 689–692
- [4] A. Carkacioglu and F. T. Yarman-Vural, "Sasi: A generic texture descriptor for image retrieval," Pattern Recognit., vol. 36, no. 11, pp. 2615–2633, 2003.
- [5] P. F. Felzenszwalb and D. P. Huttenlocher, "Efficient graph-based image segmentation," Int. J. Comput. Vis., vol. 59, no. 2, pp. 167–181, 2004.
- [6] R. Tan, K. Nishino, and K. Ikeuchi, "Color constancy through inverse- intensity chromaticity space," J. Opt. Soc. Amer. A, vol. 21, pp. 321–334, 2004.
- [7] C. Riess and E. Angelopoulou, "Scene illumination as an indicator of image manipulation," Inf. Hiding, vol. 6387, pp. 66–80, 2010.
- [8] W. R. Schwartz, A. Kembhavi, D. Harwood, and L. S. Davis, "Human detection using partial least squares analysis," in Proc. IEEE Int. Conf. Comput. Vision (ICCV), 2009, pp. 24–31.
- [9] J. Canny, "A computational approach to edge detection," IEEE Trans. Pattern Anal. Mach. Intell., vol. 8, no. 6, pp. 679–698, Jun. 1986.
- [10] G. Csurka, C. R. Dance, L. Fan, J. Willamowski, and C. Bray, "Visual categorization with bags of keypoints," in Proc. Workshop on Statistical Learning in Comput. Vision, 2004, pp. 1–8.
- [11] J. Winn, A. Criminisi, and T. Minka, "Object categorization by learned universal visual dictionary," in Proc. IEEE Int. Conf. Comput. Vision (ICCV), 2005, pp. 1800–1807.
- [12] C. M. Bishop, Pattern Recognition and Machine Learning (Information Science and Statistics). Secaucus, NJ, USA: Springer-Verlag New York, Inc, 2006.
- [13] O. A. B. Penatti, E. Valle, and R. S. Torres, "Comparative study of global color and texture descriptors for web image retrieval," J. Visual Commun. Image Representat., vol. 23, no. 2, pp. 359–380, 2012.