

Removal of Shadow from a Single Image

Shoyeb K. Pathan¹ Satish S Banait²

¹Student ²Assistant Professor

^{1,2}Department of Computer Engineering

^{1,2}K.K.Wagh College Of Engineering- Nashik, Savitribai Phule Pune University, Maharashtra, India.

Abstract— A frame work for detecting the shadow and removal of the shadow from a single image in the real world pictures. Till now the work on detecting the shadows had more effort for design of hand-craft features. Shadows distorts the image in computer pictures. For instance, the decrease of performance of objects recognition and object scene analysis. This shadow inpainting technique does not perform well in the case of non-uniform shadows. In the cases of shadows in dark environments, this method does not perform well for detecting the shadow. To address these issues the frame work consists of learning the features which are relevant. The Bayesian formulates so that the shadow inpainting is done efficiently. The method formulates so efficiently that the shadow detection process in shadowed part is detected and the shadowed region is obtained. The proposed method improves the image quality on curved surfaces and visual quality of photographs and real world images.

Key words: Bayesian shadow Inpainting, Conditional Random Field, Convolutional Neural Networks, Shadow Inpainting

I. INTRODUCTION

In computer graphics applications there are lots of algorithms for image inpainting we are going to focus on shadow inpainting. Shadows occur often in digital image, and their detection and simulation are important in many computer applications and in computer graphics. Shadows are used to get the object shape and size and to estimate the light source. Shadows cause disturbance in computer application tasks. Shadows disturb the digital image features such as image segmentation or image reconstruction and environment analysis. In digital image, detection and shadow inpainting can help in improving the quality of the digital image. By this system the shadows are detected and then inpainted by the surrounding pixels. The convolutional neural networks learn the features that are relevant to the

shadow and the features that are relevant to the boundary of the shadow region. The system detects the shadow and the non-shadow region and then the shadow region is inpainted by the pixel intensities of the surrounding pixels [1].

The shadow detection method consists of information of the shadow part and also the information of the boundary of shadowed part. As the features of the shadow part and the boundary of that part are different so the detection of shadow is separated on to two different portions. Different convolutional network layers work on different features extracted from the image or around the boundaries of the shadow part. The predictions by convolutional networks are not efficient so for this reason they are interacted with the surrounding pixels around them. Due to this reason conditional random field is involved so that assigns the labels to the graph on an image.

By the mask of the detected shadow the shadow part and the no-shadow part are considered and then the inpainting of the shadow part is completed.

A general shadow creation module is introduced for creating of the shadow and shadow free part. The shadow inpainting method or process gives a smooth surface on the shadow part that can be used for the different computer applications.

II. RELATED WORKS

A. Shadow Detection:

A famous method known to detect the shadow was the variant and invariant cue which used the static and dynamic characteristics of the shadow in an image. The features which are extracted were focused on the color chrome, texture and on the light source. Across time some works were focused on the color difference around the boundary of the shadow and the ratio of the color difference of the shadow part and around the boundary and across the boundary. These features and assumptions were useful but it was not true in all cases. For example the variant and invariant cues assume that the color intensity is different across the boundary of the shadow part and the features of texture are consistent in an image. But the approach fails when the shadow is in the dark region. And also the approach required the human effort for extraction of the features from an image and to detect the shadow. [1]

For detecting the shadows different assumptions were made which consists of the intensity of the color around the pixels and the textures intensity of the shadow part and the shadow free part.

Salvador et al. [2] consists on object shadows. In computer applications shadows interfere with the recognition of the object. Due to this issue the shadow segmentation is method is introduced in this paper. The segmentation algorithm introduced is used for the static and dynamic images. Their technique gives the physical properties to perform the task. The initial hypotheses are formulated on the fact that the shadow part is somewhat dark compared to the shadow free part. In final information it selects or does not select the region.

Joshi et al [3] in this paper they explore the technique of pixel information. It performs classification on the basis of the color intensity segmented regions. By the use of graph cut method the shadow region results are derived. The result of detection of the shadow is made by highlighting the pixels of shadow free part. A shadow free image dataset is used to compare the images which are inpainted and the image which are shadow free for verifying the result.

Vazquez et al [7] this technique can detect both the casted and self-shadow. The method exploits local color consistency properties which are cause of reflectance in excess of shadowed regions. They use all three type of

colour space in their work. Illumination edges are used to correlate local and global and low and high band of frequency. The light and colors features are given input to the adaboost to detect shadows edges. The simulation results give us an idea about the performance of the method is good with boundary marking on shadow and non shadow region with high accuracy.

B. Shadow Removal and Matting :

In time span many shadow removal techniques were implemented using information based. A famous method was to detect the shadow manually with intrinsic properties of an image. The result of this method was used to reduce the parameters of shadow removal.

Finlayson et al. [5] it address the issue of edges of the shadow part. It adds the integrating factor so as to scale the image. The integration requires the solution of 2D with the 1D Poisson distribution. The technique used was based on region based which was different from the pixel or information based. It considers individual regions separately and classification is done pair wise on the basis of intensity illumination of the regions. The classification results are used to make a graph of the regions which are segmented and the labels are given by the graph cut method. The results are then evaluated using shadow removal method and the shadow less image is obtained.

Hamiltonian path [4] proposed for shadow removal although the gradient methods does not consider for the shadow variations in the shadow regions. Simultaneously the technique of bilateral filtering was used for detection of the shadow region and boundary of the shadow region. But these techniques were time consuming and also the feature selection or parameters selection was to be done carefully so as to avoid more computation. Due to these issues new methods were introduced so as the color statistics can be transferred from the shadow less region to the shadow region.

Many assumptions were made due to the less efficient of shadow detection and removal techniques were not reliable. The camera parameters were required and in many techniques the intrinsic parameters were extracted by sequence of images.

III. ANALYSIS

A. Shadow Detection:

Convolutional neural network works on pixel level to detect the shadow in an image. There are layers which learn the different features of the shadow part of an image. After the training of the layers the output is in RGB form given as an input to give a distribution against binary class. Only the desired points are extracted as convolutional neural networks only work on equi-sized windows. The architecture of the convolutional neural network consists of convolutions and sub sampling process alternatively.

While the training process, the features are learnt automatically in a supervised discipline. The loss function is minimum used the back tracking function. The unexpected samples are used for fast learning as the neural network learns rapidly.

Shadow Removal:

The regions of the shadow and the regions of the non-shadow are to be detected. The boundary or the edge of the

shadow is also needed to be detected so as to inpaint the region properly. The detection of shadow part and the boundary of shadowed part helps in simplifying the errors. The works which were done before need to be processed manually through human interaction. The proposed system simply works to produce the shadow and the boundary of the shadow part and non shadowed part. The object shadow boundary is not visible in the dark regions or in dark environment. The inpainting of the shadow boundary is done efficiently until the boundary of shadow of the object is as large as the total shadow boundary.

Shadow region is inpainted by using the neighbor pixel intensity. The shadowed region is removed or inpainted by the surrounding pixels.

IV. SUMMARY & CONCLUSION:

An approach that is data driven which learns the relevant features for the detection of shadows from a single image. In the proposed shadow removal system, the shadow matte is extracted within the image. A Bayesian formulation consists of the basis of shadow removal process and makes use of an improved shadow generation model. Shadow detection uses the combination of boundary and region convolutional neural network with the CRF model. For shadow removal, the multi-level color transfer followed by the Bayesian refinement is used. The proposed framework has a number of applications including image editing and image enhancement tasks.

ACKNOWLEDGEMENT

I am glad to express my sentiments of gratitude to all who rendered their valuable help for the successful completion of the paper. I am thankful to my guide Prof. S. S. Banait, Assistant Professor, Computer Engineering, K.K.W.I.E.E.R., Nashik for his guidance and encouragement. His expert suggestions and scholarly feedback had greatly enhanced the effectiveness. I would also like to thank to Prof. Dr. S. S. Sane, Head, Department of Computer Engineering, K.K.W.I.E.E.R., Nashik.

REFERENCES

- [1] D. H. Hubel and T. N. Wiesel, "Receptive fields, binocular interaction and functional architecture in the cat's visual cortex," *The Journal of Physiology*, vol. 160, no. 1, p. 106, 1962.
- [2] E. Salvador, A. Cavallaro, and T. Ebrahimi, "Cast shadow segmentation using invariant color features," *CVIU*, vol. 95, no. 2, pp. 238–259, 2004.
- [3] A. J. Joshi and N. P. Papanikolopoulos, "Learning to detect moving shadows in dynamic environments," *TPAMI*, vol. 30, no. 11, pp. 2055–2063, 2008.
- [4] I. Huerta, M. Holte et al., "Detection and removal of chromatic moving shadows in surveillance scenarios," in *ICCV. IEEE*, 2009, pp. 1499–1506.
- [5] G. D. Finlayson, S. D. Hordley, C. Lu, and M. S. Drew, "On the removal of shadows from images," *TPAMI*, vol. 28, no. 1, pp. 59–68, 2006.
- [6] G. D. Finlayson, S. D. Hordley, and M. S. Drew, "Removing shadows from images," in *ECCV*, vol. 2353. Springer, 2002, pp. 823–836.

- [7] E. Vazquez, R. Baldrich et al., “Describing reflectances for color segmentation robust to shadows, highlights, and textures,” TPAMI, vol. 33, no. 5, pp. 917–930, 2011.
- [8] A. Bousseau, S. Paris, and F. Durand, “User-assisted intrinsic images,” in TOG, vol. 28, no. 5. ACM, 2009.
- [9] G. D. Finlayson, S. D. Hordley, C. Lu, and M. S. Drew, “On the removal of shadows from images,” TPAMI, vol. 28, no. 1, pp. 59–68, 2006.
- [10] G. D. Finlayson, S. D. Hordley, and M. S. Drew, “Removing shadows from images,” in ECCV, vol. 2353. Springer, 2002, pp. 823–836.
- [11] G. D. Finlayson, M. S. Drew, and C. Lu, “Entropy minimization for shadow removal,” IJCV, vol. 85, no. 1, pp. 35–57, 2009.
- [12] C. Fredembach and G. D. Finlayson, “Hamiltonian path based shadow removal.” in BMVC, 2005, pp. 502–511.
- [13] F. Liu and M. Gleicher, “Texture-consistent shadow removal,” in ECCV. Springer, 2008, pp. 437–450.
- [14] A. Mohan, J. Tumblin, and P. Choudhury, “Editing soft shadows in a digital photograph,” Computer Graphics and Applications, IEEE, vol. 27, no. 2, pp. 23–31, 2007.
- [15] E. Arbel and H. Hel-Or, “Shadow removal using intensity surfaces and texture anchor points,” TPAMI, vol. 33, no. 6, pp. 1202–1216, 2011.
- [16] V. Kwatra, M. Han, and S. Dai, “Shadow removal for aerial imagery by information theoretic intrinsic image analysis,” in ICCP. IEEE, 2012, pp. 1–8.

